



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

PINO S2

S2+CI+HI+HRO+FO+SR

EN UNE ISO 20345:2022/A1:2024



Description

Welding type safety boot, padded collar, with polyurethane and nitrile rubber sole and quick release buckle fastening system.

Upper

Black cowhide leather with a thickness quality of 2.0-2.2 mm.

Lining

Upper and heel: in anti-allergic polyamide-based material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foamed material with textile support, ergonomic design according to biomechanical gait patterns.

Outsole

Antistatic nitrile rubber, anti-slip design. Anti-torsion pads, orange color, which protrude from the sole and provide such effect. These properties are achieved by the design of the sole, which has a wide contact surface, heel type pads for soft soils, brake area and channels for dirt and grease evacuation. Low density antistatic foamed polyurethane midsole with high cushioning capacity. Provides thermal insulation.

Toe cap: steel, with impact resistance of 200 J.

Fastening system: Buckle.


Height: 120 mm $\pm$ 5% (Size 42)

Sizes: 35-50 EU/2-15 UK

Weight: 1.30 kg/Par $\pm$ 5% (Size 42)



Leather



Textile material



TOE RESISTANT
TO 200 J



NON-SLIP SOLE



HYDROCARBON
RESISTANT