



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

ABETO

S3+CI+HI+HRO+SRC

EN UNE ISO 20345:2011



Description

Ankle safety boot, padded collar and tongue, with polyurethane and antistatic nitrile rubber sole.

Upper

Black full grain cowhide with a quality thickness of 2.0 – 2.2 mm.

Lining

Anti-allergic polyester base material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

Outsole

Anti-static nitrile rubber, anti-slip design. Anti-twist pads, grey in colour, protruding from the sole and provide this effect. These properties are achieved by the design of the sole which has a large contact surface, soft ground cleats, brake area and dirt and grease evacuation channels. Midsole Polyurethane Foam Antistatic low density with high cushioning capacity. Provides thermal insulation.

Protective insole: metallic, with perforation resistance > 1.100 N.

Toe cap: steel, with impact resistance of 200 J.

Fastening system: laces.


Height: 140 mm ± 5% (Size 42)

Sizes: 35-50 EU/2-15 UK

Weight: 1.50 kg/Pair ± 5% (Size 42)



Leather



Textile material



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT