



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

CEDRO S2 ESD

S2+CI+HI+FO+SR

EN UNE ISO 20345:2022/A1:2024



Description

Safety shoe, padded collar and tongue, with polyurethane dual density sole.

Upper

Black full grain cowhide with a thickness of 2,0-2,2 mm.

Lining

Made from anti-allergic polyamide material, highly resistant to abrasion, absorption and drying of perspiration.

Insole

Made of foamed material with textile support, ergonomic design based on biomechanical walking motions.

Outsole

Compact Polyurethane Antistatic, high density, biomechanical and anti-slip design, with anti-roll pads. Midsole Polyurethane Foam Antistatic low density with high cushioning capacity. Provides thermal insulation.

Toe cap: non-metallic, with impact resistance of 200 J.

Fastening system: Elastics.


Height: 78 mm $\pm$ 5% (Size 42)

Sizes: 35-50 EU/2-15 UK

Weight: 1.05 kg/Pair $\pm$ 5% (Size 42)



Leather



Textile material



TOE RESISTANT
TO 200 J



NON-SLIP SOLE



HYDROCARBON
RESISTANT