



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

ACEBO CM

S1+P+SRC

EN UNE ISO 20345:2011



Description

Perforated safety low shoe, padded collar and tongue, with polyurethane dual-density sole.

Upper

Split nubuck blue cowhide with a quality thickness of 1.8- 2.0 mm.

Lining

Anti-allergic polyester base material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

Outsole

Compact Polyurethane Antistatic, high density, biomechanical and anti-slip design, with anti-roll pads. Midsole Polyurethane Foam Antistatic low density with high cushioning capacity. Provides thermal insulation.

Protective insole: textile, with perforation resistance > 1.100 N.

Toe cap: non-metallic, with impact resistance of 200 J.


Fastening system: laces. **Height:** 85 mm $\pm$ 5% (Size 42)

Sizes: 35-48 EU/2-13 UK

Weight: 1.20 kg/pair $\pm$ 5% (Size 42)



Nubuck



Textile Material



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT