



**ROBUSTA**  
STEP FORWARD

**CALZADOS ROBUSTA, S.L**

Crtra de Préjano, 72  
Arnedo, La Rioja, 26580  
T +34 941 38 54 11  
www.robusta.es

## EBANO VLCO

**S3L+CI+HI+FO+SR**

**EN UNE ISO 20345:2022**



### Description

Ankle safety boot, padded collar and tongue, with polyurethane dual-density sole.

### Upper

Black full grain cowhide with a thickness of 2.0–2.2 mm.

### Lining

Anti-allergic polyamide base material, with high resistance to abrasion, absorption and drying of perspiration.

### Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

### Outsole

Antistatic, high density compact polyurethane with high abrasion resistance. Antislip design with channels for dirt and grease evacuation. Low-density antistatic foamed polyurethane midsole with high shock absorption capacity. Provides thermal insulation.

**Protective insole:** textile, with perforation resistance >1.100 N.

**Toe cap:** non-metallic, with impact resistance of 200 J.


**Fastening system:** vlco.

**Height:** 120 mm ± 5% (Size 42)

**Sizes:** 35-48 EU/2-13 UK



Leather



Textile Material



TOE RESISTANT  
TO 200 J



ANTI-PERFORATION  
INSOLE



NON-SLIP SOLE



HYDROCARBON  
RESISTANT