



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

SANDALO

S1+P+CI+HI+SRC

EN UNE ISO 20345:2011



Description

Perforated safety shoe, padded collar and tongue, with polyurethane dual-density sole.

Upper

Split Nubuck leather in brown with a thickness of 2.0–2.2 mm.

Lining

Anti-allergic polyamide base material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

Outsole

Antistatic, high density compact polyurethane with high abrasion resistance. Antislip design with channels for dirt and grease evacuation. Low-density antistatic foamed polyurethane midsole with high shock absorption capacity. Provides thermal insulation.

Protective insole: textile, with perforation resistance >1.100 N.

Toe cap: non-metallic, with impact resistance of 200 J.


Fastening system: vlco.

Height: 60 mm ± 5% (Size 42)

Sizes: 35-48 EU/2-13 UK



Nubuck



Textile Material



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT