



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

WELDER

S3L+CI+HI+FO+HRO+SR

EN UNE ISO 20345:2022/A1:2024



Description

Low-cut safety boot, welder style, padded collar, with polyurethane and nitrile rubber sole.

Upper

Black cowhide leather with a thickness of 2.0–2.2 mm.

Lining

Anti-allergic polyamide base material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

Outsole

Antistatic nitrile rubber sole, biomechanical and non-slip design, with anti-roll pads (anti-torsion system). Provides greater force absorption during the impact phase and stability of the footfall, uniformity of footfall and pronation control while walking. Low-density antistatic foamed polyurethane midsole with high shock absorption capacity. Provides thermal insulation.

Protective insole: textile, with perforation resistance >1.100 N.

Toe cap: non-metallic, with impact resistance of 200 J.


Fastening system: vlco.

Height: 120 mm ± 5% (Size 42)

Sizes: 35-48 EU/2-13 UK



Leather



Textile Material



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT