



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

METAERGONOMIC

S3+CI+HI+FO+M+SR

EN UNE ISO 20345:2022/A1:2024



Description

Low safety boot, padded collar, metatarsal protection device, with anti-static, dual-density polyurethane sole.

Upper

Black full grain cowhide with a thickness of 2.0–2.2 mm.

Lining

Anti-allergic polyamide base material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

Outsole

Antistatic, high density compact polyurethane with high abrasion resistance. Antislip design with channels for dirt and grease evacuation. Low-density antistatic foamed polyurethane midsole with high shock absorption capacity. Provides thermal insulation.

Protective insole: steel, with perforation resistance >1.100 N.

Toe cap: steel, with impact resistance of 200 J.


Fastening system: laces.

Height: 120 mm ± 5% (Size 42)

Sizes: 35-50 EU/2-15 UK



Leather



Textile Material



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT