



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

ENEBRO DIELECTRICO

SB+PL+CI+HI+E+WPA+FO+HRO+SR

EN UNE ISO 20345:2022/A1:2024



Description

Safety shoe, padded collar and tongue, with polyurethane sole and dielectric nitrile rubber.

Upper

Black full grain cowhide with a thickness of 2.0–2.2 mm.

Lining

Anti-allergic polyamide base material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

Outsole

Dielectric nitrile rubber sole, biomechanical, non-slip design with anti-tip pads (antitorsion system). Improves dynamic adaptation over previous model by at least 15% (half-foot torsion and torsion of metatarsals). Provides greater absorption of forces in impact phase, step stability/uniformity and pronation control while walking. Low-density antistatic foamed polyurethane midsole with high shock absorption capacity. Provides thermal insulation.

This shoe has been tested as per ASTM F2413:2018 American standard to ensure the footwear is shockproof. Specifically, when voltages of 18,000 volts at a 60-Hz frequency are applied for one minute, the current is below 1 mA under the conditions described in said standards

Protective insole: textile, with perforation resistance >1.100 N.

Toe cap: non-metallic, with impact resistance of 200 J.


Fastening system: laces.

Height: 77 mm ± 5% (Size 42)

Sizes: 35-48 EU/2-13 UK



Leather



Textile Material



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT