

PETO

S3+CI+HI+WR+SRC

EN UNE ISO 20345:2011



Description

Low safety shoe, padded collar and tongue, with polyurethane dual-density sole.

Upper

Black full grain cowhide with a thickness of 2.0 - 2.2 mm.

Lining

Waterproof and breathable Gore-Tex®, dual component based on PTFE+PU.

Insole

Anti-bacteria designed entirely by our Biomechanics Laboratory, with an ergonomic design according to the distribution of plantar pressures, arch support, retro capital support and confinement of the soft tissues of the heel, providing comfort, rest and absence of humidity inside the heel. footwear. Anti-bacteria, antistatic and breathable treatment.

Outsole

Antistatic, high density compact polyurethane with high abrasion resistance. Antislip design with channels for dirt and grease evacuation. Low-density antistatic foamed polyurethane midsole with high shock absorption capacity. Provides thermal insulation

Protective insole: textile, with perforation resistance >1.100 N.

Toe cap: non-metallic, with impact resistance of 200 J.

Fastening system: laces.

Height: 80 mm ± 5% (Size 42)

Sizes: 35-48 EU/2-13 UK



Leather



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT