



ROBUSTA
STEP FORWARD

CALZADOS ROBUSTA, S.L

Crtra de Préjano, 72
Arnedo, La Rioja, 26580
T +34 941 38 54 11
www.robusta.es

DIAMOND FLUOR S153

S3L+CI+HI+FO+SR

EN UNE ISO 20345:2022



Description

Safety shoe, padded collar and tongue, with double density polyurethane sole.

Upper

PU-coated technical fabric, highly resistant to abrasion and cuts. Waterproof and breathable. Easy cleaning and maintenance.

Lining

Anti-allergic polyester base material, with high resistance to abrasion, absorption and drying of perspiration.

Insole

Foam material with textile support, ergonomic design according to biomechanical running patterns.

Outsole

Compact Polyurethane Antistatic, high density, biomechanical and anti-slip design, with anti-roll pads. Midsole Polyurethane Foam Antistatic low density with high cushioning capacity. Provides thermal insulation.

Protective insole: Textile with perforation resistance > 1.100 N.


Toe cap: Non-metallic, with impact resistance of 200 J.

Fastening system: laces.

Height: 85 mm $\pm$ 5% (Size 42)

Sizes: 35-48 EU/2-13 UK

Weight: 1.10 kg/Pair $\pm$ 5% (Size 42)



Textile material



TOE RESISTANT
TO 200 J



ANTI-PERFORATION
INSOLE



NON-SLIP SOLE



HYDROCARBON
RESISTANT